

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

Identity (As used on Label and List) TempTAB 300, TempTAB 600	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

Section I – Product Identification

Manufacturer's Name The Edward Orton Jr. Ceramic Foundation	Emergency Telephone Number (614) 895-2663 ext 1343
Address (Number, Street, City, State, & Zip Code) 6991 Old 3C Highway Westerville OH 43082	Telephone Number for Information (614) 895-2663
Date Prepared 5/8/08	Signature of Preparer (Optional) <i>Thomas McInerney</i>

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	(%) (Optional)
Silica as dust (respirable)		10 mg/m ³		trace
Aluminum Oxide	10 mg/m ³	10 mg/m ³		1-25
Anhydrous Borax	10 mg/m ³	10 mg/m ³		1-50
Borax, 5 mol	10 mg/m ³	10 mg/m ³		1-70
Calcium Carbonate	10 mg/m ³	10 mg/m ³		1-50
Barium Carbonate	.5 mg/m ³ (as Ba)			1-40
Fluorides (inorganic)	2.5 mg/m ³ (as F)			1-10
Silica	10 mg/m ³			1-50

Section III – Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H ₂ O = 1)	1.8 – 2.0
Vapor Pressure (mmHg)	N/A	Melting Point	N/A
Vapor Density (Air = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	Nil		
Appearance and Color	Round disk with 1/8" hole in center		

Section IV – Fire And Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media N/A			
Special Fire Fighting Procedures All products except those labeled Fast Fire or PCE contain 4-6% organic material that will oxidize above 300°F			
Unusual Fire and Explosion Hazards N/A			